

PRODUCT INFORMATION FOR THE BUILDING CERTIFICATION SCHEME LEED V4[®] (Leadership in Energy and Environmental Design)

The intention of this document is to support project teams pursuing LEED v4 certification by providing an overview of how your products contribute to LEED v4 credits. This information is based on Leed v4 credit library (2014 -07)¹

Armaflex

General Information

Company name:	Armacell GmbH
Address:	Robert-Bosch-Str. 10, 48153 Münster
Contact person:	Hubert Helms
Phone:	+49 (0)251 760 3278
Email:	hubert.helms@armacell.com
Homepage:	www.armacell.com
Date:	01.06.2015

Product information

Product description

This fact sheets covers six product brands of the product family Armaflex:
NH/Armaflex, SH/Armaflex, HT/Armaflex, Armaflex Ultima, AF/Armaflex, AF/Armaflex Class O

Armaflex products are the professional, highly flexible, closed-cell elastomeric foam insulation (FEF) for continuous energy saving and condensation control purposes. The combination of very low thermal conductivity and extremely high resistance to water vapour transmission prevents long-term energy losses and water vapour ingress and reduces the risk of corrosion under insulation.

Application

Armaflex is used to insulate pipes, air ducts and vessels including fittings and flanges of industrial installations and building equipment.

¹ <http://www.usgbc.org/credits> (8/2014)

Technical data

Product brand	Water vapour diffusion resistance	Thermal conductivity	Maximum service temperature	Minimum service temperature	Reaction to fire
Standard/Unit	EN 12088 [-]	[W/mK]	EN 14706/7 [°C]	EN 14706/7 [°C]	EN 135001-1 [-]
NH/Armaflex	≥ 2000	0,040 (0 °C)	+110	-50	Tubes: D _L -s3, d0/ Sheets: E
SH/Armaflex		0.036/0.040 (40 °C)	+110	-50	Tubes: B _L -s3, d0/ C _L -s3, d0 Sheets: C-s3, d0/ D-s3, d0
HT/Armaflex	≥ 4000 / ≥ 3000	0.042 / 0.045 (40 °C)	+110	-50	Tubes: D _L -s3, d0/ Sheets: D-s3, d0
Armaflex Ultima	7000	0.040 (0 °C)	+110	-50	Tubes: B _L -s1, d0/ Sheets: B-s2, d0
AF/Armaflex	≥ 10000 / ≥ 7000	0.033 / 0036 (0 °C)	+110	-50	Tubes: B _L -s3, d0/ Sheets: B-s3, d0
AF/Armaflex Class O	≥ 10000 / ≥ 7000	0.033 / 0.036 (0 °C)	+110	-50	Tubes: B _L -s3, d0/ Sheets: B-s3, d0

Product declarations

Environmental product declaration
Number:

NH/Armaflex - EPD-ARM-20150106-IBB1-DE
 SH/Armaflex – EPD-ARM-20150107-IBB1-DE
 HT/Armaflex – EPD-ARM-20150108-IBB1-DE
 Armaflex Ultima – EPD-ARM-20150109-IBB1-DE
 AF/Armaflex – EPD-ARM-20150060-IBB1-DE
 AF/Armaflex Class O – EPD-ARM-2015-0110-IBB1-DE
 NH/Armaflex - EPD-ARM-20150106-IBB1-DE
 Institut Bauen und Umwelt e.V. (IBU), Berlin, Germany
 thinkstep AG, Leinfelden-Echterdingen, Germany

Programme operator:
Author of the LCA:

Materials and Resources (MR)

Summary

Materials and Resources credits encourage the use of sustainable building materials and the reduction of waste. Indoor environmental quality credits promote better indoor air quality and access to daylight and views.

Building product disclosure and optimization - environmental product declarations

Intent of this credit

To encourage the use of products and materials for which life cycle information is available and that have environmentally, economically, and socially preferable life cycle impacts. To reward project teams for selecting products from manufacturers who have verified improved environmental life cycle impacts.

Product information for the declared product within this credit:

Item	Value
Critically reviewed LCA acc. to ISO 14044?	yes
Reviewer	Institut Bauen und Umwelt e.V. (IBU), Berlin, Germany
Download link of the document/study	https://epd-online.com/
Industry-wide (generic) EPD (Type III, including external verification)?	no
Product specific EPD (Type III, including external verification)?	yes
EPD programme operator	Institut Bauen und Umwelt e.V. (IBU), Berlin, Germany; www.construction-environment.com
EPD programme operator country	Germany
EPD number	See table product declaration
Declared unit	1 m ³

Results of the LCA – ENVIRONMENTAL IMPACTS:

NH/Armaflex 1 m³ / 62.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard EN 15804)	A1-A3	A4	A5	C2	C4	D
GWP [kg CO ₂ -Äquiv.]	307.494	4.628	57.503	0.286	159.851	-49.310
ODP [kg CFC11-Äq.]	9.137E-09	1.904E-11	1.807E-10	1.177E-12	1.319E-09	-1.689E-08
AP [kg SO ₂ -Äq.]	5.928E-01	1.189E-02	1.060E-02	7.349E-04	2.171E-01	-1.314E-01
EP [kg PO ₄ -- Äq.]	1.192E-01	2.935E-03	1.721E-03	1.814E-04	7.541E-03	-8.901E-03
POCP [kg Ethen Äq.]	1.379E-01	-3.219E-03	1.608E-03	-1.989E-04	4.860E-03	-1.078E-02
Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources					

SH/Armaflex 1 m³ / 47.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard EN 15804)	A1-A3	A4	A5	C2	C4	D
GWP [kg CO ₂ -Äquiv.]	213.538	3.019	34.844	0.217	121.486	-36.722
ODP [kg CFC11-Äq.]	1.025E-08	1.242E-11	1.630E-10	8.942E-13	1.002E-09	-1.258E-08
AP [kg SO ₂ -Äq.]	9.711E-01	7.755E-03	1.306E-02	5.585E-04	1.650E-01	-9.786E-02
EP [kg PO ₄ -- Äq.]	9.684E-02	1.915E-03	1.326E-03	1.379E-04	5.731E-03	-6.629E-03
POCP [kg Ethen Äq.]	4.388E-01	-2.099E-03	4.579E-03	-1.512E-04	3.693E-03	-8.027E-03
Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources					

HT/Armaflex 1 m³ / 75 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard EN 15804)	A1-A3	A4	A5	C2	C4	D
GWP [kg CO ₂ -Äquiv.]	309.211	5.113	58.448	0.343	191.821	-57.798
ODP [kg CFC11-Äq.]	1.267E-08	2.103E-11	2.199E-10	1.412E-12	1.582E-09	-1.980E-08
AP [kg SO ₂ -Äq.]	2.354E+00	1.314E-02	2.887E-02	8.819E-04	2.605E-01	-1.540E-01
EP [kg PO ₄ -- Äq.]	1.455E-01	3.243E-03	2.010E-03	2.177E-04	9.049E-03	-1.043E-02
POCP [kg Ethen Äq.]	2.741E-01	-3.555E-03	2.992E-03	-2.387E-04	5.832E-03	-1.263E-02
Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources					

factsheets

Armaflex Ultima 1 m³ / 57.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard EN 15804)	A1-A3	A4	A5	C2	C4	D
GWP [kg CO ₂ -Äquiv.]	232.710	3.792	41.888	0.263	147.063	-43.915
ODP [kg CFC11-Äq.]	7.966E-09	1.560E-11	1.468E-10	1.082E-12	1.213E-09	-1.504E-08
AP [kg SO ₂ -Äq.]	5.688E-01	9.743E-03	9.518E-03	6.761E-04	1.997E-01	-1.170E-01
EP [kg PO ₄₃ -- Äq.]	9.816E-02	2.405E-03	1.382E-03	1.669E-04	6.937E-03	-7.927E-03
POCP [kg Ethen Äq.]	1.528E-01	-2.637E-03	1.705E-03	-1.830E-04	4.471E-03	-9.599E-03
Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources					

AF/Armaflex 1 m³ / 52.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared stages (standard EN 15804)	A1-A3	A4	A5	C2	C4	D
GWP [kg CO ₂ -Äquiv.]	264.092	3.661	43.639	0.240	134.274	-40.853
ODP [kg CFC11-Äq.]	1.061E-08	1.506E-11	1.727E-10	9.883E-13	1.108E-09	-1.400E-08
AP [kg SO ₂ -Äq.]	1.307E+00	9.405E-03	1.702E-02	6.173E-04	1.823E-01	-1.089E-01
EP [kg PO ₄₃ -- Äq.]	1.165E-01	2.322E-03	1.548E-03	1.524E-04	6.334E-03	-7.374E-03
POCP [kg Ethen Äq.]	2.481E-01	-2.546E-03	2.673E-03	-1.671E-04	4.082E-03	-8.930E-03
Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources					

AF/Armaflex Class O 1 m³ / 52.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard EN 15804)	A1-A3	A4	A5	C2	C4	D
GWP [kg CO ₂ -Äquiv.]	230.364	1.057	36.981	0.240	134.274	-41.176
ODP [kg CFC11-Äq.]	1.007E-08	4.349E-12	1.688E-10	9.883E-13	1.108E-09	-1.411E-08
AP [kg SO ₂ -Äq.]	1.275E+00	2.716E-03	1.678E-02	6.173E-04	1.823E-01	-1.097E-01
EP [kg PO ₄₃ -- Äq.]	1.082E-01	6.706E-04	1.457E-03	1.524E-04	6.334E-03	-7.433E-03
POCP [kg Ethen Äq.]	1.313E+00	-7.352E-04	1.345E-02	-1.671E-04	4.082E-03	-9.001E-03
Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources					

factsheets

Results of the LCA – RESOURCE USE:

NH/Armaflex 1 m³ / 62.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard DIN EN 15804)	A1-A3	A4	A5	C2	C4	D
PE total [MJ]	7388.568	67.607	83.720	4.178	350.416	-928.036
PERE [MJ]	1627.093	-	-	-	-	-
PERM [MJ]	0	-	-	-	-	-
PERT [MJ]	1627.093	3.574	17.270	0.221	36.469	-85.211
PENRE [MJ]	4736.475	-	-	-	-	-
PENRM [MJ]	1025.000	-	-	-	-	-
PENRT [MJ]	5761.475	64.033	66.450	3.957	313.947	-842.826
SM [kg]	45.026	0	0.455	0	0	0
RSF [MJ]	-	-	-	-	-	-
NRSF [MJ]	-	-	-	-	-	-
FW [kg]	1654.506	6.273	67.878	0.388	330.871	-172.017

Caption

PE total = Total use of primary energy resources (=PERT+PENRT); PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

SH/Armaflex 1 m³ / 47.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard DIN EN 15804)	A1-A3	A4	A5	C2	C4	D
PE total [MJ]	5199.792	44.093	58.847	3.175	266.316	-691.107
PERE [MJ]	1016.805	-	-	-	-	-
PERM [MJ]	0	-	-	-	-	-
PERT [MJ]	1016.805	2.331	10.856	0.168	27.717	-63.449
PENRE [MJ]	3313.737	-	-	-	-	-
PENRM [MJ]	869.250	-	-	-	-	-
PENRT [MJ]	4182.987	41.762	47.991	3.008	238.599	-627.658
SM [kg]	25.188	0	0.254	0	0	0
RSF [MJ]	-	-	-	-	-	-
NRSF [MJ]	-	-	-	-	-	-
FW [kg]	1746.481	4.091	51.614	0.295	251.462	-128.086

Caption

PE total = Total use of primary energy resources (=PERT+PENRT); PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

factsheets

HT/Armaflex 1 m³ / 75 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard DIN EN 15804)	A1-A3	A4	A5	C2	C4	D
PE total [MJ]	7643.700	74.682	87.126	5.014	420.499	-1087.772
PERE [MJ]	1628.272	-	-	-	-	-
PERM [MJ]	0	-	-	-	-	-
PERT [MJ]	1628.272	3.948	17.364	0.265	43.763	-99.864
PENRE [MJ]	4650.428	-	-	-	-	-
PENRM [MJ]	1365.000	-	-	-	-	-
PENRT [MJ]	6015.428	70.734	69.762	4.749	376.736	-987.907
SM [kg]	45.541	0	0.460	0	0	0
RSF [MJ]	-	-	-	-	-	-
NRSF [MJ]	-	-	-	-	-	-
FW [kg]	1945.354	6.929	72.030	0.465	397.045	-201.599

Caption

PE total = Total use of primary energy resources (=PERT+PENRT); PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

Armaflex Ultima 1 m³ / 57.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard DIN EN 15804)	A1-A3	A4	A5	C2	C4	D
PE total [MJ]	5316.377	55.392	61.018	3.844	322.383	-826.477
PERE [MJ]	1228.254	-	-	-	-	-
PERM [MJ]	0	-	-	-	-	-
PERT [MJ]	1228.254	2.928	13.085	0.203	33.552	-75.872
PENRE [MJ]	2236.623	-	-	-	-	-
PENRM [MJ]	1851.500	-	-	-	-	-
PENRT [MJ]	4088.123	52.464	47.933	3.641	288.831	-750.605
SM [kg]	32.459	0	0.328	0	0	0
RSF [MJ]	-	-	-	-	-	-
NRSF [MJ]	-	-	-	-	-	-
FW [kg]	1859.118	5.140	56.330	0.357	304.401	-153.165

Caption

PE total = Total use of primary energy resources (=PERT+PENRT); PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

factsheets

AF/Armaflex 1 m³ / 52.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard DIN EN 15804)	A1-A3	A4	A5	C2	C4	D
PE total [MJ]	6186.695	53.475	68.476	3.510	294.349	-768.861
PERE [MJ]	1268.847	-	-	-	-	-
PERM [MJ]	0	-	-	-	-	-
PERT [MJ]	1268.847	2.827	13.380	0.186	30.634	-70.590
PENRE [MJ]	4020.098	-	-	-	-	-
PENRM [MJ]	897.750	-	-	-	-	-
PENRT [MJ]	4917.848	50.648	55.096	3.324	263.715	-698.271
SM [kg]	33.613	0	0.340	0	0	0
RSF [MJ]	-	-	-	-	-	-
NRSF [MJ]	-	-	-	-	-	-
FW [kg]	1959.900	4.962	58.482	0.326	277.932	-142.502

Caption

PE total = Total use of primary energy resources (=PERT+PENRT); PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

AF/Armaflex Class O 1 m³ / 52.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard DIN EN 15804)	A1-A3	A4	A5	C2	C4	D
PE total [MJ]	5616.149	15.444	62.675	3.510	294.349	-774.953
PERE [MJ]	975.119	-	-	-	-	-
PERM [MJ]	0	-	-	-	-	-
PERT [MJ]	975.119	0.816	10.428	0.186	30.634	-71.157
PENRE [MJ]	3743.281	-	-	-	-	-
PENRM [MJ]	897.750	-	-	-	-	-
PENRT [MJ]	4641.031	14.627	52.247	3.324	263.715	-703.796
SM [kg]	24.423	0	0.247	0	0	0
RSF [MJ]	-	-	-	-	-	-
NRSF [MJ]	-	-	-	-	-	-
FW [kg]	1772.929	1.433	57.712	0.326	277.932	-143.645

Caption

PE total = Total use of primary energy resources (=PERT+PENRT); PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

Results of the LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

NH/Armaflex 1 m³ / 62.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard DIN EN 15804)	A1-A3	A4	A5	C2	C4	D
HWD [kg]	1.741E-03	3.038E-05	2.057E-05	1.878E-06	1.371E-04	-2.429E-04
NHWD [kg]	3.391E+01	9.116E-03	1.426E+00	5.634E-04	9.887E+01	-2.520E-01
RWD [kg]	1.432E-01	8.749E-05	1.867E-03	5.407E-06	1.340E-02	-6.058E-02
CRU [kg]	-	-	-	-	-	-
MFR [kg]	1.689	0	53.815	0	0	-
MER [kg]	-	-	-	-	-	-
EEE [MJ]	0	0	26.389	0	141.550	-
EET [MJ]	0	0	61.429	0	333.925	-
Caption	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier					

SH/Armaflex 1 m³ / 47.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard DIN EN 15804)	A1-A3	A4	A5	C2	C4	D
HWD [kg]	1.115E-02	1.981E-05	1.147E-04	1.427E-06	1.042E-04	-1.809E-04
NHWD [kg]	1.599E+01	5.945E-03	9.721E-01	4.282E-04	7.514E+01	-1.877E-01
RWD [kg]	1.136E-01	5.706E-05	1.438E-03	4.109E-06	1.018E-02	-4.511E-02
CRU [kg]	-	-	-	-	-	-
MFR [kg]	0.659	0	30.102	0	0	-
MER [kg]	-	-	-	-	-	-
EEE [MJ]	0	0	17.471	0	107.578	-
EET [MJ]	0	0	40.674	0	253.783	-
Caption	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier					

HT/Armaflex 1 m³ / 75 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard DIN EN 15804)	A1-A3	A4	A5	C2	C4	D
HWD [kg]	2.969E-02	3.356E-05	3.032E-04	2.253E-06	1.646E-04	-2.847E-04
NHWD [kg]	2.945E+01	1.007E-02	1.580E+00	6.761E-04	1.186E+02	-2.954E-01
RWD [kg]	1.447E-01	9.665E-05	1.912E-03	6.489E-06	1.608E-02	-7.100E-02
CRU [kg]	-	-	-	-	-	-
MFR [kg]	1.314	0	54.426	0	0	-
MER [kg]	-	-	-	-	-	-
EEE [MJ]	0	0	26.958	0	169.859	-
EET [MJ]	0	0	62.760	0	400.710	-
Caption	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier					

Armaflex Ultima 1 m³ / 57.5 kg/m³

Life cycle stages	A 1-A3	A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary
Declared life cycle stages (standard DIN EN 15804)	A1-A3	A4	A5	C2	C4	D
HWD [kg]	1.321E-03	2.489E-05	1.580E-05	1.727E-06	1.262E-04	-2.163E-04
NHWD [kg]	2.917E+01	7.469E-03	1.272E+00	5.183E-04	9.096E+01	-2.244E-01
RWD [kg]	1.209E-01	7.168E-05	1.551E-03	4.975E-06	1.233E-02	-5.394E-02
CRU [kg]	-	-	-	-	-	-
MFR [kg]	0.000	0	38.783	0	0	-
MER [kg]	-	-	-	-	-	-
EEE [MJ]	0	0	19.306	0	130.226	-
EET [MJ]	0	0	44.949	0	307.211	-
Caption	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier					

AF/Armaflex 1 m³ / 52.5 kg/m³

Life cycle stages	A 1-A3		A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary	
Declared life cycle stages (standard DIN EN 15804)	A1-A3	A4	A5	C2	C4	D	
HWD [kg]	1.822E-02	2.403E-05	1.902E-04	1.577E-06	1.152E-04	-2.012E-04	
NHWD [kg]	2.456E+01	7.210E-03	1.154E+00	4.732E-04	8.305E+01	-2.088E-01	
RWD [kg]	1.342E-01	6.920E-05	1.651E-03	4.542E-06	1.126E-02	-5.018E-02	
CRU [kg]	-	-	-	-	-	-	
MFR [kg]	0.892	0	40.171	0	0	-	
MER [kg]	-	-	-	-	-	-	
EEE [MJ]	0	0	20.221	0	118.902	-	
EET [MJ]	0	0	47.073	0	280.497	-	
Caption	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier						

AF/Armaflex Class O 1 m³ / 52.5 kg/m³

Life cycle stages	A 1-A3		A 4-5		C1-4		D
	Product stage	Construction process stage		End-of-life stage		Benefits and loads beyond the system boundary	
Declared life cycle stages (standard DIN EN 15804)	A1-A3	A4	A5	C2	C4	D	
HWD [kg]	1.702E-02	6.940E-06	1.778E-04	1.577E-06	1.152E-04	-2.028E-04	
NHWD [kg]	1.182E+01	2.082E-03	1.100E+00	4.732E-04	8.305E+01	-2.105E-01	
RWD [kg]	1.378E-01	1.999E-05	1.700E-03	4.542E-06	1.126E-02	-5.059E-02	
CRU [kg]	-	-	-	-	-	-	
MFR [kg]	2.768	0	29.210	0	0	-	
MER [kg]	-	-	-	-	-	-	
EEE [MJ]	0	0	21.339	0	118.902	-	
EET [MJ]	0	0	49.632	0	280.497	-	
Caption	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier						

factsheets

Building product disclosure and optimization – sourcing of raw materials

Intent of this credit

To encourage the use of products and materials for which life cycle information is available and that have environmentally, economically, and socially preferable life cycle impacts. To reward project teams for selecting products verified to have been extracted or sourced in a responsible manner.

Product information for the declared product within this credit:

Option 1: Raw material source and extraction reporting	
Third-party verified corporate sustainability report (CSR)?	no
Link to download the report	-
Option 2: Leadership extraction practices (1 point)	
Description / Unit	
Participation in an extended producer responsibility programme?	Yes: Global compact - www.unglobalcompact.org
Bio-based products meet the Sustainable Agriculture Network's Sustainable Agriculture Standard?	not applicable
Wood products certified by the Forest Stewardship Council or USGBC-approved equivalent?	not applicable
Materials reuse	Production residues are partly used for the production of ArmaSound. ArmaSound is a high-performance sound absorption product made by Armacell for a quieter environment.
Post-consumer recycled content	0 %
Pre-consumer recycled content	0 %

Building product disclosure and optimization – material ingredients

Intent of this credit

To encourage the use of products and materials for which life cycle information is available and that have environmentally, economically, and socially preferable life cycle impacts. To reward project teams for selecting products for which the chemical ingredients in the product are inventoried using an accepted methodology and for selecting products verified to minimize the use and generation of harmful substances. To reward raw material manufacturers who produce products verified to have improved life cycle impacts.

Product information for the declared product within this credit:

Type of reporting	Certification programme (e.g. Green screen, cradle-to-cradle version/level, REACH)	Value/Comment
Material ingredient optimization	International Alternative Compliance Path – REACH Optimization	According to the European Chemicals Regulation (REACH) manufacturer, importers and downstream users must register their chemicals and are responsible for their safe use on their own. For its production Armacell uses exclusively verifiably registered and approved substances / mixtures. Products manufactured and marketed by Armacell do not have to be registered. The products may contain traces of azodicarbonamide (ACDA). Possible minimal residual amounts are included in the polymer matrix. A health impairment can be excluded. For the production of insulation materials based on synthetic rubber, there is currently no alternative to ADCA available.
	USGBC approved programme	Yes: Armacell LEED Scorecard

Indoor Environmental Quality (IEQ)

Summary

Indoor environmental quality credits promote better indoor air quality and access to daylight and views.

Low-emitting materials

Intent of this credit

To reduce concentrations of chemical contaminants that can damage air quality, human health, productivity, and the environment.

Product information for the declared product within this credit:

Interior paints and coatings, interior adhesives and sealants, flooring products:

Item	Value
Test institute / organization (Name)	Eurofins Product Testing A/S
Test method applied	ISO 16000-3/6/9/11 – loading factor 0.5 m ² /m ³
Applicable regulation / Criteria	AgBB
Regulation requirements met	yes
IEQ Credit 3.2 (NC, Schools / 1 Point) Construction IAQ Management Plan - Before Occupancy	Armaflex is fibre-free, non-eroding, formaldehyde-free and low-VOC

Acoustic performance

Intent of this credit

To provide workspaces and classrooms that promote occupants' well-being, productivity, and communications through effective acoustic design.

Product information for the declared product within this credit:

Product	Structure-borne sound transmission	Test Standard
AF/Armaflex	≤ 28 dB (A)	ISO 3822-1
	Weighted sound absorption coefficient	
	≤ 0,45	ISO 11654

Disclaimer:

The content of, and results shown in, this report are based on data and information submitted by the client. Therefore, PE International AG makes no representation or warranty, express or implied, in regard of the correctness or completeness of the content of this document or the results shown.