

BREEAM COMPLIANCE PRODUCT CARD

Technical insulation



TECHNICAL
INSULATION



COOLING



AIR
CONDITIONING

NH/ArmaFlex Smart

NH/ArmaFlex Smart is a Halogen free, flexible closed-cell insulation material for building equipment and industrial installations¹.

BREEAM International New Construction 2013

BREEAM is a multi-criteria scheme to assess and certify buildings. Established in UK, it emphasises sustainable development by promoting green, healthy and eco-friendly buildings. Features of the buildings which may be assessed are: materials, quality of indoor environments and energy efficiency etc. Nowadays it has become a standard in real estates markets.

BREEAM compliance product card for NH/ArmaFlex Smart was prepared to assist designers, architects, engineers, consultants and developers to provide clear information and to facilitate choosing proper product. Appropriate BREEAM categories related to NH/ArmaFlex Smart features were chosen and checked. NH/ArmaFlex Smart compliance and contribution to BREEAM categories are presented below.



Product compliant



Product contributes to a better rating

BREEAM Category	Issue	BREEAM Requirements	Credits	Product compliance
Life cycle cost and service life planning	Man 05	A life cycle cost and service life planning analysis of the building components should be carried out in order to obtain their full information through all the life cycle.	3 ••	NH/ArmaFlex Smart life cycle information may be a part of the building analysis. The following data may be useful: - life cycle durability: as the service life of the equipment or the whole building (>50 years), - restrictions: insulation thicknesses are available for all common pipe diameters up to an outer diameter of 114 mm for tubes; temperature range: -50 °C to +110 °C, - recycling: non-recyclable, - costs: during installation and utilization (no costs while in use), - comparison to natural rubber: better temperature resistance - less heat/cold losses and extremely constant quality. More information may be found in Environmental Product Declaration. ²
Life cycle impacts	Mat 01	An environmental impact of construction materials over the building life cycle should be specified by using an appropriate life cycle assessment (LCA) tool.	7 ••	Data useful for life cycle assessment (LCA) may be found in Environmental Product Declaration (EPD) ³ . Life cycle assessment in EPD has been carried out in GaBi Software (LCA tool), which is based on ISO 14025 standard and addresses the whole life cycle of product, including disposal.
Insulation	Mat 04	Construction materials should be responsibly sourced. A responsibly sourced confirmation of „supply chain process“ and „key process“ should be provided.	1 •	NH/ArmaFlex Smart is responsibly sourced which may be confirmed with ISO14001 ³ certificates for: - supply chain process (polymer) - key process (insulation production).
Thermal comfort	Hea 03	A thermal comfort analysis should be carried out to assess if the indoor environment maintains comfortable conditions for building users in terms of appropriate thermal comfort level according to ISO 7730:2005.	2 ••	NH/ArmaFlex Smart is a part of building's systems. Adjusting proper design parameters will enable to improve energy efficiency and its supply to the system appliances. For energy efficiency the main parameter of NH/ArmaFlex Smart is thermal conductivity $\lambda_{0°C} \leq 0,040 \text{ W/mK}$. ¹
Reduction of energy use and carbon emissions	Ene 01	An energy performance should be carried out to assess building energy consumption during operation in comparison with the notional building (parameters defined by national standards).	15 ••	
Energy efficient cold storage	Ene 05	Greenhouse gas emissions from cold storage systems should be reduced by improving their energy efficiency.	3 ••	

For detailed information please refer to the documents provided by manufacturer:

¹ NH/ArmaFlex Smart product card

² Environmental Product Declaration: EPD-ARM-20150106-IBB1-DE3

³ ISO 14001 certificates are available for the factories in Muenster (Germany), Środa Śląska (Poland), Begur (Spain) as well as for main polymers production.

• NH/ArmaFlex Smart has a direct impact on the following categories. While using NH/ArmaFlex Smart with another appropriate products - credits stated above may be awarded. Maximum number of credits influenced by the product for each category was stated above.

•• NH/ArmaFlex Smart has an indirect impact on the following categories. Using NH/ArmaFlex Smart with another appropriate products may contribute to achieve credits. Maximum number of credits influenced by the product for each category was stated above.

BREEAM COMPLIANCE PRODUCT CARD

Technical insulation



TECHNICAL INSULATION



COOLING



AIR CONDITIONING

NH/ArmaFlex Smart

NH/ArmaFlex Smart is a Halogen free, flexible closed-cell insulation material for building equipment and industrial installations¹.

BREEAM International New Construction 2016

BREEAM is a multi-criteria scheme to assess and certify buildings. Established in UK, it emphasises sustainable development by promoting green, healthy and eco-friendly buildings. Features of the buildings which may be assessed are: materials, quality of indoor environments and energy efficiency etc. Nowadays it has become a standard in real estates markets.

BREEAM compliance product card for NH/ArmaFlex Smart was prepared to assist designers, architects, engineers, consultants and developers to provide clear information and to facilitate choosing proper product. Appropriate BREEAM categories related to NH/ArmaFlex Smart features were chosen and checked. NH/ArmaFlex Smart compliance and contribution to BREEAM categories are presented below.



BREEAM Category	Issue	BREEAM Requirements	Credits	Product compliance
Life cycle cost and service life planning	Man 02	A life cycle cost and service life planning analysis of the building components and elements should be carried out in order to obtain their full information through all the life cycle.	3 ••	NH/ArmaFlex Smart life cycle information may be a part of the building analysis. The following data may be useful: - life cycle durability: as the service life of the equipment or the whole building (>50 years), - restrictions: insulation thicknesses are available for all common pipe diameters up to an outer diameter of 114 mm for tubes; temperature range: -50 °C to +110 °C, - recycling: non-recyclable, - costs: during installation and utilization (no costs while in use), - comparison to natural rubber: better temperature resistance - less heat/cold losses and extremely constant quality. More information may be found in Environmental Product Declaration. ²
Indoor air quality: Minimising sources of air pollution	Hea 02	At least four of five finishing materials should meet appropriate volatile organic compounds (VOC) emission levels and confirm compliance with testing standards ISO 10580, ISO 16000-9, CEN/TS 16516 or CDPH Standard Method v1.1. VOC emission limits for insulation were listed in Tables 17 and 18 of BREEAM International NC 2016 Manual.	3 •	Sampling, testing and evaluation were performed according to ISO 16000-9. Insulation meets exemplary level emission limits: ³ - Formaldehyde ≤ 0,01 mg/m ³ - Total volatile organic compounds ≤ 0,3 mg/m ³ - Total semi-volatile organic compounds ≤ 0,1 mg/m ³ - Category 1A and 1B carcinogens ≤ 0,001 mg/m ³
Life cycle impacts	Mat 01	An environmental impact of construction materials over the building life cycle should be specified by using an appropriate life cycle assessment (LCA) tool.	5 ••	Data useful for life cycle assessment (LCA) may be found in EPD ⁴ . Life cycle assessment in EPD has been carried out in GaBi Software (LCA tool), which is based on ISO 14025 standard and addresses the whole life cycle of product, including disposal.
		At least five products out of ten material categories, including insulation products, should have Environmental Products Declarations (EPD). In one material category maximum two products' EPDs may be counted. The EPD must be compliant with ISO 14025, ISO 21930 or EN 15804.	2 •	Using NH/ArmaFlex Smart with other products having EPD will help to score a credit. NH/ArmaFlex Smart EPD ⁴ is compliant with ISO 14025 and ISO 15804.
Responsible sourcing of construction	Mat 03	Construction materials should be responsibly sourced. A responsibly sourced confirmation of „supply chain process“ and „key process“ should be provided.	4 •	NH/ArmaFlex Smart is responsibly sourced which may be confirmed with ISO14001 ⁵ certificates for: - supply chain process (polymer) - key process (insulation production).
Material efficiency	Mat 06	In order to minimise materials' environmental impact more efficient materials should be used during building design, procurement, construction, maintenance and end of life.	1 ••	NH/ArmaFlex Smart as a part of building energy system has the following efficiency features: - a service life is more than 50 years, - it may be damaged only by extraordinary impacts or during installation, - varied packaging: appropriate size and package type (2 m tubes, tapes and sheets). Packaging waste is reduced.
Thermal comfort	Hea 04	A thermal comfort analysis should be carried out to assess if the indoor environment maintains comfortable conditions for building users in terms of appropriate thermal comfort level according to ISO 7730:2005.	3 ••	NH/ArmaFlex Smart is a part of building's systems. Adjusting proper design parameters will enable to improve energy efficiency and its supply to the system appliances. For energy efficiency the main parameter of NH/ArmaFlex Smart is thermal conductivity $\lambda_{0°C} < 0,040$ W/mK. ⁶
Reduction of energy use and carbon emissions	Ene 01	An energy performance should be carried out to assess building energy consumption during operation in comparison with the following requirements: notional building (parameters defined by national standards) and BREEAM best practice building (BREEAM defined parameters).	15 ••	
Energy efficient cold storage	Ene 05	Greenhouse gas emissions from cold storage systems should be reduced by improving their energy efficiency.	3 ••	

For detailed information please refer to the documents provided by manufacturer:

¹ NH/ArmaFlex Smart product card

² Environmental Product Declaration: EPD-ARM-20220037-1BB1-EN

³ Eurofins Product Testing A/S attestation and test report no. 392-2021-00552403_A_EN and 392-2021-00552404_A_EN

⁴ ISO 14001 certificates are available for the factories in Muenster (Germany), Środa Śląska (Poland), Begur (Spain) as well as for main polymers production.

• NH/ArmaFlex Smart has a direct impact on the following categories. While using NH/ArmaFlex Smart with another appropriate products - credits stated above may be awarded. Maximum number of credits influenced by the product for each category was stated above.

•• NH/ArmaFlex Smart has an indirect impact on the following categories. Using NH/ArmaFlex Smart with another appropriate products may contribute to achieve credits. Maximum number of credits influenced by the product for each category was stated above.

LEED COMPLIANCE PRODUCT CARD

Technical insulation



TECHNICAL
INSULATION



COOLING



AIR
CONDITIONING

NH/ArmaFlex Smart

NH/ArmaFlex Smart is a Halogen free, flexible closed-cell insulation material for building equipment and industrial installations¹.

LEED 2009

for Green Building Design and Construction

LEED is a multi-criteria scheme to assess and certify buildings. Established in USA, it emphasises sustainable development by promoting green, healthy and eco-friendly buildings. Features of the buildings which may be assessed are: materials, quality of indoor environments and energy efficiency etc. Nowadays it has become a standard in real estates markets.

LEED compliance product card for NH/ArmaFlex Smart was prepared to assist designers, architects, engineers, consultants and developers to provide clear information and to facilitate choosing proper product. Appropriate LEED categories related to NH/ArmaFlex Smart features were chosen and checked. NH/ArmaFlex Smart compliance and contribution to LEED categories are presented below.



Product compliant



Product contributes to a better rating

LEED Issue	Credit	LEED Requirements	Points	Product compliance
EA	Prerequisite 2	Minimum Energy Performance	-	NH/ArmaFlex Smart is a part of building's systems. Adjusting proper design parameters will enable to improve energy efficiency and its supply to the system appliances. For energy efficiency the main parameter of the NH/ArmaFlex Smart product is thermal conductivity $\lambda_{pC} \leq 0,040$ W/mK
EA	Credit 1	Optimize Energy Performance	21 ••	
IEQ	Credit 3.2	Construction Indoor Air Quality Management Plan – before occupancy	1 ••	NH/ArmaFlex Smart may contribute reducing air contamination. Sampling, testing and evaluation of the product determine low levels of formaldehyde and VOC. ²
IEQ	Credit 7.1	Thermal Comfort	1 ••	NH/ArmaFlex Smart has got an indirect impact on achieving acceptable range of operative temperature and humidity by providing protection for pipes or air ducts. Therefore it prevents condensation of the humidified air. Water vapour diffusion resistance of the product is $\mu \geq 2000$. ¹
IEQ	Credit 7.2	Thermal Comfort – Verification	1 ••	

For detailed information please refer to the documents provided by manufacturer:

¹ NH/ArmaFlex Smart product card

² Eurofins Product Testing A/S attestation and test report data

• NH/ArmaFlex Smart has an indirect impact on the following categories. Using NH/ArmaFlex Smart with another appropriate products may contribute to achieve credits. Maximum number of credits influenced by the product for each category was stated above.

LEED COMPLIANCE PRODUCT CARD

Technical insulation



TECHNICAL
INSULATION



COOLING



AIR
CONDITIONING

NH/ArmaFlex Smart

NH/ArmaFlex Smart is a Halogen free, flexible closed-cell insulation material for building equipment and industrial installations.¹

LEED v4

for Green Building Design and Construction

LEED is a multi-criteria scheme to assess and certify buildings. Established in USA, it emphasises sustainable development by promoting green, healthy and eco-friendly buildings. Features of the buildings which may be assessed are: materials, quality of indoor environments and energy efficiency etc. Nowadays it has become a standard in real estates markets.





LEED compliance product card for NH/Armaflex was prepared to assist designers, architects, engineers, consultants and developers to provide clear information and to facilitate choosing proper product. Appropriate LEED categories related to NH/Armaflex features were chosen and checked. NH/Armaflex compliance and contribution to LEED categories are presented below.



Product compliant



Product contributes to a better rating

LEED Issue	Credit	LEED Requirements	Points	Product compliance
EA	Prerequisite Minimum Energy Performance	Option 1. Whole-building energy simulation	-	NH/ArmaFlex Smart is a part of building's systems. Adjusting proper design parameters will enable to improve energy efficiency and its supply to the system appliances. For energy efficiency the main parameter of the NH/ArmaFlex Smart product is thermal conductivity $\lambda_{pTC} < 0,040 \text{ W/mK}$. ¹
EA	Optimize Energy Performance	Option 1. Whole-building energy simulation	18**	
EQ	Thermal Comfort	Thermal Comfort Design Option 2. ISO and CEN Standards	1**	
MR	Building Product Disclosure and Optimization – Environmental Product Declarations	Option 1. Environmental Product Declarations (EPD)	1•	NH/ArmaFlex Smart has got an EPD ² with a third party certification (Type III) in accordance to ISO 14025 and EN 15804 and includes an external verification. Acradle to grave scope has been provided. 
EQ	Low-Emitting Materials	Option 1. Product category calculations	3•	NH/ArmaFlex Smart has been tested ³ in accordance to: ISO 16000-3/6/9/11:2010 in conjunction with the German AgBB Testing and Evaluation Scheme (2012), DIBt (2010) and French legislation on VOC emission class. Product complies with limit values of the AgBB and DIBt regulations. For the French regulation emission class is A+. 
EQ	Thermal Comfort	Thermal Comfort Design Option 1. ASHRAE Standard 55-2010	1**	NH/ArmaFlex Smart has an indirect impact on achieving acceptable range of operative temperature and humidity by providing protection for pipes or air ducts. Therefore it prevents condensation of the humidified air. Water vapour diffusion resistance of the product is $\mu 2 000$. ⁴ 

¹ For detailed information please refer to the documents provided by manufacturer:

² NH/ArmaFlex Smart product card

³ Environmental Product Declaration: EPD-ARM-20220037-1BB1-EN

⁴ Eurofins Product Testing A/S attestation and test report no. 392-2021-00552403_A_EN and 392-2021-00552404_A_EN

• NH/ArmaFlex Smart has a direct impact on the following categories. While using NH/ArmaFlex Smart with another appropriate products - credits stated above may be awarded. Maximum number of credits influenced by the product for each category was stated above.

•• NH/ArmaFlex Smart has an indirect impact on the following categories. Using NH/ArmaFlex Smart with another appropriate products may contribute to achieve credits. Maximum number of credits influenced by the product for each category was stated above.