

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Armaflex RS850

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Adhesive for processing all flexible Armaflex insulation materials

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

Armacell GmbH
Robert-Bosch-Straße 10
48153 Münster

Telephone no. +49 (0) 251 - 7603-200

Fax no. +49 (0) 251 - 7603-561

e-mail info.de@armacell.com

Information provided by / telephone

Dr. Heribert Quante, Tel.: +49 (0) 251 - 7603-227

Advice on Safety Data Sheet

heribert.quante@armacell.com

Address

Armacell UK Ltd
Mars Street
OL9 6LY Oldham
United Kingdom

email: info.armaform@armacell.com

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 3; H412

Eye Irrit. 2; H319

Flam. Liq. 2; H225

Skin Irrit. 2; H315

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07

Signal word

Danger

Hazardous component(s) to be indicated on label:

butanone

ethyl-acetate

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

methylcyclohexane
acetone

Hazard statement(s)

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Hazard statements (EU)

EUH208 Contains Rosin; colophony. May produce an allergic reaction.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection.
P312 Call a POISON CENTER/doctor if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

Vapours can form an explosive mixture with air.

PBT assessment
No data available.

vPvB assessment
No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	butanone			
	78-93-3 201-159-0 606-002-00-3 01-2119457290-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 25.00 - < 50.00	wt%
2	ethyl-acetate			
	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	EUH066 Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	>= 25.00 - < 50.00	wt%
3	methylcyclohexane		pls. refer to footnote (1)	
	108-87-2 203-624-3 601-018-00-7 01-2119556887-18	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 10.00 - < 25.00	wt%
4	acetone			
	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 10.00 - < 25.00	wt%
5	Rosin; colophony			
	8050-09-7 232-475-7 650-015-00-7 01-2119480418-32	Skin Sens. 1; H317	< 1.00	wt%
6	zinc oxide			
	1314-13-2 215-222-5 030-013-00-7 -	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 1.00	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

When inhaled remove to fresh air and seek medical aid.

After skin contact

When in contact with the skin, clean with soap and water.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart and seek medical advice.

After ingestion

Do not induce vomiting. Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray jet; Carbon dioxide; Dry chemical extinguisher; Foam

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Do not inhale vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. In case of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up rest with absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). When collected, handle material as described under the section heading "Disposal considerations".

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary).

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - refrain from smoking. Take precautionary measures against static charges.

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

Storage stability

Value 36 months

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage.

Incompatible products

Do not store together with: explosive substances; spontaneously combusting substances

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
	2000/39/EC		
	Butanone		
	WEL short-term (15 min reference period)	900	mg/m ³ 300 ppm
	WEL long-term (8-hr TWA reference period)	600	mg/m ³ 200 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	Butan-2-one		
	WEL short-term (15 min reference period)	899	mg/m ³ 300 ppm
	WEL long-term (8-hr TWA reference period)	600	mg/m ³ 200 ppm
	Comments	Sk, BMGV	
2	ethyl-acetate	141-78-6	205-500-4
	2017/164/EU		
	Ethyl acetate		
	WEL short-term (15 min reference period)	1468	mg/m ³ 400 ppm
	WEL long-term (8-hr TWA reference period)	734	mg/m ³ 200 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	Ethyl acetate		
	WEL short-term (15 min reference period)		400 ppm
	WEL long-term (8-hr TWA reference period)		200 ppm
3	acetone	67-64-1	200-662-2
	2000/39/EC		
	Acetone		
	WEL long-term (8-hr TWA reference period)	1210	mg/m ³ 500 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	Acetone		
	WEL short-term (15 min reference period)	3620	mg/m ³ 1500 ppm
	WEL long-term (8-hr TWA reference period)	1210	mg/m ³ 500 ppm
4	Rosin; colophony	8050-09-7	232-475-7
	List of approved workplace exposure limits (WELs) / EH40		
	Rosin-based solder flux fume		
	WEL short-term (15 min reference period)	0.15	mg/m ³
	WEL long-term (8-hr TWA reference period)	0.05	mg/m ³
	Comments	Sen	

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	butanone			78-93-3 201-159-0	
	dermal	Long term (chronic)	systemic	1161	mg/kg/day
	inhalative	Long term (chronic)	systemic	600.00	mg/m ³
2	ethyl-acetate			141-78-6 205-500-4	
	dermal	Long term (chronic)	systemic	63	mg/kg/day
	inhalative	Short term (acut)	systemic	1468	mg/m ³

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

	inhalative	Long term (chronic)	local	734	mg/m ³
	inhalative	Short term (acut)	local	1468	mg/m ³
	inhalative	Long term (chronic)	systemic	734	mg/m ³
3	acetone			67-64-1 200-662-2	
	dermal	Long term (chronic)	systemic	186	mg/kg/day
	inhalative	Short term (acut)	local	2420	mg/m ³
	inhalative	Short term (acut)	systemic	1210	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	butanone			78-93-3 201-159-0	
	oral	Long term (chronic)	systemic	31	mg/kg/day
	dermal	Long term (chronic)	systemic	412	mg/kg/day
	inhalative	Long term (chronic)	systemic	106	mg/m ³
2	ethyl-acetate			141-78-6 205-500-4	
	oral	Long term (chronic)	systemic	4.5	mg/kg/day
	dermal	Long term (chronic)	systemic	37	mg/kg/day
	inhalative	Short term (acut)	systemic	734	mg/m ³
	inhalative	Long term (chronic)	local	367	mg/m ³
	inhalative	Short term (acut)	local	734	mg/m ³
	inhalative	Long term (chronic)	systemic	367	mg/m ³
3	acetone			67-64-1 200-662-2	
	oral	Long term (chronic)	systemic	62	mg/kg/day
	dermal	Long term (chronic)	systemic	62	mg/kg/day
	inhalative	Long term (chronic)	systemic	200	mg/m ³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	butanone		78-93-3 201-159-0	
	water	fresh water	55.8	mg/L
	water	marine water	55.8	mg/L
	water	Aqua intermittent	55.8	mg/L
	water	fresh water sediment	284.74	mg/kg
	with reference to: dry weight			
	water	marine water sediment	284.7	mg/kg
	with reference to: dry weight			
	soil	-	22.5	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	709	mg/L
	secondary poisoning	-	1000	mg/kg
	with reference to: food			
2	ethyl-acetate		141-78-6 205-500-4	
	water	fresh water	0.24	mg/L
	water	marine water	0.024	mg/L
	water	Aqua intermittent	1.65	mg/L
	water	fresh water sediment	1.15	mg/kg dry weight
	water	marine water sediment	0.115	mg/kg dry weight
	soil	-	0.148	mg/kg dry weight
	sewage treatment plant	-	650	mg/L
	secondary poisoning	-	200	mg/kg
3	acetone		67-64-1 200-662-2	
	water	fresh water	10.6	mg/L
	water	Aqua intermittent	21	mg/L
	water	marine water	1.06	mg/L
	water	fresh water sediment	30.4	mg/kg
	water	marine water sediment	3.04	mg/kg
	soil	-	29.5	mg/kg
	sewage treatment plant	-	100	mg/L

8.2 Exposure controls

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of insufficient ventilation and during spray application respiratory protection necessary. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness	0.6	- 0.8	mm
Breakthrough time	60	- 120	min

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation		
liquid		
Form/Colour		
pasty		
yellow		
Odour		
characteristic		
pH value		
No data available		
Boiling point / boiling range		
Value	55	°C
Melting point/freezing point		
No data available		
Decomposition temperature		
No data available		
Flash point		
Value	-17	°C
Ignition temperature		
Value	260	°C
Auto-ignition temperature		
Comments	Product is not selfigniting.	
Explosive properties		
The product does not have explosive properties.		
Flammability		
No data available		
Lower explosion limit		
Value	1.1	% vol
Upper explosion limit		
Value	11.5	% vol
Vapour pressure		
Value	105	hPa
Reference temperature	20	°C
Relative vapour density		

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

No data available			
Relative density			
No data available			
Density			
Value	0.842	g/cm ³	
Reference temperature	20	°C	
Solubility in water			
Comments	immiscible		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
	log Pow	0.3	
	Reference temperature	40	°C
	Method	OECD 117	
	Source	ECHA	
2	ethyl-acetate	141-78-6	205-500-4
	log Pow	6.8	
	Reference temperature	25	°C
	Source	ECHA	
3	acetone	67-64-1	200-662-2
	log Pow	-0.23	
	Method	QSAR	
	Source	ECHA	
Viscosity			
Value	8500	mPa*s	
Reference temperature	20	°C	
Type	dynamic		
Solvent content			
Value	80.4	%	
Solids content			
Value	19.5	%	
Particle characteristics			
No data available			

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

Dangerous reactions are not expected if the product is handled according to its intended use.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

None, when used as directed.

10.4 Conditions to avoid

No data available.

10.5 Incompatible materials

strong oxidizing agents

10.6 Hazardous decomposition products

None, if handled according to intended use.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

1	butanone	78-93-3	201-159-0
LD50		2054	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA / Read across		
2	ethyl-acetate	141-78-6	205-500-4
LD50	>	5600	mg/kg bodyweight
Species	rat		
Source	ECHA		
3	acetone	67-64-1	200-662-2
LD50		5800	mg/kg bodyweight
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
4	zinc oxide	1314-13-2	215-222-5
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity

No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
LD50	>	20000	mg/kg bodyweight
Species	rabbit		
Source	ECHA		
2	acetone	67-64-1	200-662-2
LD50	>	15800	mg/kg bodyweight
Species	rabbit		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Acute inhalational toxicity

No	Substance name	CAS no.	EC no.
1	acetone	67-64-1	200-662-2
LC50		76	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation

No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Duration of exposure		4	h
Species	rabbit		
Method	OECD 404		
Source	ECHA / Read across		
Evaluation	non-irritant		
2	ethyl-acetate	141-78-6	205-500-4
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	low-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	acetone	67-64-1	200-662-2
Species	guinea pig		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Serious eye damage/irritation

No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		
2	ethyl-acetate	141-78-6	205-500-4
Species	rabbit		

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

Method	OECD 405
Source	ECHA
Evaluation	low-irritant
3	acetone 67-64-1 200-662-2
Species	rabbit
Method	OECD 405
Source	ECHA
Evaluation	irritant
Evaluation/classification	Based on available data, the classification criteria are met.
Respiratory or skin sensitisation	
No	Substance name CAS no. EC no.
1	butanone 78-93-3 201-159-0
Route of exposure	Skin
Species	guinea pig
Method	OECD 406
Source	ECHA
Evaluation	non-sensitizing
2	ethyl-acetate 141-78-6 205-500-4
Route of exposure	Skin
Species	guinea pig
Method	OECD 406
Source	ECHA
Evaluation	non-sensitizing
3	acetone 67-64-1 200-662-2
Route of exposure	Skin
Species	guinea pig
Source	ECHA
Evaluation	non-sensitizing
Evaluation/classification	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	
No	Substance name CAS no. EC no.
1	butanone 78-93-3 201-159-0
Type of examination	in vitro gene mutation study in bacteria
Species	Salmonella typhimurium
Method	OECD 471
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Type of examination	In vitro Mammalian Chromosomal Aberration Test
Species	rat
Method	OECD 473
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Type of examination	In vitro mammalian cell gene mutation test
Species	Mouse lymphoma cells
Method	OECD 476
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Type of examination	In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus
Species	mouse
Method	OECD 474
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
2	acetone 67-64-1 200-662-2
Type of examination	in vitro gene mutation study in bacteria
Species	Salmonella typhimurium
Method	OECD 471
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Type of examination	In vitro Mammalian Chromosomal Aberration Test
Species	Chinese hamster Ovary (CHO)
Method	OECD 473
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Type of examination	in vitro gene mutation study in mammalian cells
Species	Mouse lymphoma cells
Method	OECD 476
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Route of exposure		inhalational	
Type of examination		Prenatal Developmental Toxicity Study	
Species		rat	
Method		OECD 414	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	acetone	67-64-1	200-662-2
Route of exposure		inhalational	
NOAEC		2200	ppm
Type of examination		Prenatal Developmental Toxicity Study	
Species		rat	
Method		OECD 414	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	acetone	67-64-1	200-662-2
Route of exposure		dermal	
Type of examination		Toxicity study	
Species		mouse	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
STOT - single exposure			
No data available			
STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Route of exposure		inhalational	
Species		rat	
Method		OECD 413	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	acetone	67-64-1	200-662-2
Route of exposure		oral	
NOAEL		10000	ppm
Species		rat	
Method		OECD 408	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Route of exposure		inhalational	
NOAEC		19000	ppm
Species		rat	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Aspiration hazard			
No data available			
Delayed and immediate effects as well as chronic effects from short and long-term exposure			
Inhalation of the vapours causes irritation of the respiratory tract and mucous membrane, headaches, nausea, giddiners, vomiting.			

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
LC50		2993	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
2	ethyl-acetate	141-78-6	205-500-4
LC50		230	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Source	ECHA		
3	acetone	67-64-1	200-662-2
LC50		5540	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
EC50		308	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
2	ethyl-acetate	141-78-6	205-500-4
EC50		1350	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		
3	acetone	67-64-1	200-662-2
EC50		8800	mg/l
Duration of exposure		48	h
Species	Daphnia pulex		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
EC50		2029	mg/l
Duration of exposure		96	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
Type	aerobic biodegradation		
Value		98	%
Duration		28	day(s)
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		
2	ethyl-acetate	141-78-6	205-500-4
Source	ECHA		

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

Evaluation	readily biodegradable		
3	acetone	67-64-1	200-662-2
Type	aerobic biodegradation		
Value		90.9	%
Duration		28	day(s)
Method	OECD 301 B		
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
log Pow		0.3	
Reference temperature		40	°C
Method	OECD 117		
Source	ECHA		
2	ethyl-acetate	141-78-6	205-500-4
log Pow		6.8	
Reference temperature		25	°C
Source	ECHA		
3	acetone	67-64-1	200-662-2
log Pow		-0.23	
Method	QSAR		
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	No data available.
vPvB assessment	No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not discharge into drains or waters and do not dispose of in public landfills.
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	III
UN number	UN1133
Proper shipping name	ADHESIVES
Tunnel restriction code	E
Label	3
Comments	Classification in packing group III according to ADR (chapter 2.2.3.1.4)

14.2 Transport IMDG

Class	3
Packing group	III

Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

UN number	UN1133
Proper shipping name	ADHESIVES
EmS	F-E, S-D
Label	3
Comments	Classification in packing group III according to IMDG-Code (chapter 2.3.3.2.3)

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	III
UN number	UN1133
Proper shipping name	Adhesives
Label	3
Comments	Classification in packing group III according to IATA-DGR, chapter 3.3.3.1.1

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P5c
--	-----

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content	80.4	%
-------------	------	---

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Further information

Authors responsible for the compilation of the material safety data sheet: UMCO GmbH - D-21107 Hamburg, Georg-Wilhelm-Strasse 187, Tel.: +49(40)555 546 300, Fax: +49(40)555 546 357, e-mail: umco@umco.de.

The information is based on our current knowledge however it does not represent a guarantee of product properties nor does it create any legal obligation.

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH066	Repeated exposure may cause skin dryness or cracking.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.



Trade name: Armaflex RS850

Current version : 4.1.0, issued: 05.08.2021

Replaced version: 4.0.0, issued: 27.04.2021

Region: GB

H410
H411

Very toxic to aquatic life with long lasting effects.
Toxic to aquatic life with long lasting effects.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.
Prod-ID 636642