



◆ 친 환경 , 최고의 난연등급 고무발포보온재 Armaflex ◆

Armaflex Class1

▣TUBE [Armacell Armaflex Class '1'] Weight

단열재 TUBE I.D	호 칭 경				단 열 재 두께별 무게 (KG 기준이며, 포장 무게를 제외한 수치임.)																		
	Steel(강관)		Copper(동관)		9T			13T			19T			25T			32T			40T			
	A	Inch	A	Inch	M/CTN	KG/CTN	KG/EA	M/CTN	KG/CTN	KG/EA	M/CTN	KG/CTN	KG/EA	M/CTN	KG/CTN	KG/EA	M/CTN	KG/CTN	KG/EA	M/CTN	KG/CTN	KG/EA	
6			6	1/4				180	9.32	0.104	112	7.77	0.139										
10			8	3/8	264	8.02	0.061	144	8.56	0.119	100	8.06	0.161	60	6.82	0.227							
12			10	1/2	220	7.61	0.069	128	7.90	0.123	90	7.39	0.164				32	7.30	0.456				
15			15	5/8	180	6.95	0.077	112	8.30	0.148	80	7.94	0.199	48	6.25	0.260	32	7.83	0.489				
20			18	3/4	144	6.21	0.086	100	7.30	0.146	72	8.45	0.235	40	6.07	0.304	24	6.09	0.508	22			
22	15	1/2	20	7/8	128	6.53	0.102	90	7.59	0.169	60	7.34	0.245	40	6.48	0.324	24	6.59	0.549	18	7.37	0.819	
25				1	108	6.21	0.115	82	6.92	0.169	50	6.93	0.277	36	6.31	0.351				18			
28	20	3/4	25	1 1/8	98	6.06	0.124	72	6.92	0.192	40	6.14	0.307	32	6.71	0.419	22	7.33	0.666	16	7.16	0.895	
32				1 1/4	84	5.59	0.133	64	6.20	0.194	40	6.75	0.338	24	5.90	0.492	20	7.16	0.716				
35	25	1	32	1 3/8	82	5.85	0.143	58	6.71	0.231	36	6.73	0.374	24	6.40	0.533	18	7.17	0.797	12	7.85	1.308	
38				1 1/2	72	5.40	0.150	54	6.05	0.224	34	6.88	0.405	24	6.55	0.546				16			
42	32	1 1/4	40	1 5/8	60	4.77	0.159	48	6.65	0.277	28	5.01	0.358	22	6.47	0.588	16	5.31	0.664	12	6.40	1.067	
45				1 3/4				40	5.46	0.273	24	5.34	0.445	20	6.13	0.613				16			
48	40	1 1/2		1 7/8	50	4.39	0.176	40	5.94	0.297	24	5.92	0.493	20	5.80	0.580	12	6.05	1.008	12			
54			50	2(2 1/8)	40	3.36	0.168	36	5.08	0.282	24	6.46	0.538	20	5.88	0.588	10	5.38	1.076	10	6.07	1.214	
60	50	2		2 3/8	32	3.14	0.196	28	4.89	0.349	20	5.21	0.521	16	4.62	0.578	10	5.64	1.128	10	6.47	1.294	
67			65	2 1/2(2 5/8)	32	3.17	0.198	24	4.67	0.389	16	5.01	0.626	14	5.12	0.731	8	4.69	1.173	8	5.52	1.380	
76	65	2 1/2		2 7/8(3)				22	4.71	0.428	14	4.12	0.589	12	4.86	0.810	8	5.47	1.368	8	5.96	1.490	
80			80	3 1/8				18	4.55	0.506	14	4.26	0.609	12	3.91	0.652	8	5.50	1.375	8			
89	80	3		3 1/2				18	4.39	0.488	12	4.11	0.685	12	4.41	0.735	8	6.50	1.625	8	4.95	1.238	
108			100	4				16	2.65	0.331	10	3.97	0.794	8	5.60	1.400	6	5.64	1.880	6	5.68	1.893	
114	100	4						16	2.97	0.371	10	4.33	0.866	6	4.29	1.430	4	3.51	1.755	4	3.94	1.970	

▣SHEET [Armacell Armaflex Class '1'] Weight

ITEM	SIZE	KG/CTN
06000CS (6T)	W1.4m X L20m	7.41
09000CS (9T)	W1.4m X L10m	9.48
13000CS (13T)	W1.4m X L20m	17.33
19000CS (19T)	W1.4m X L10m	12.72
25000CS (25T)	W1.4m X L6m	10.03
32000CS (32T)	W1.0m X L6m	14.18
40000CS (40T)	W1.0m X L2m	10.99

▣Accessories

ITEM	SIZE	EA/BOX	KG/EA
850 Adhesive	1kg/1can	20	1
PVC Tape	50mm * 50m	20	0.5
PVC Tape	75mm * 50m	13	0.75

▣10M coil Weight

SIZE	KG/CTN	SIZE	KG/CTN
9T * 6.35	4	13T * 6.35	4
9T * 9.52	4	13T * 9.52	4
9T * 12.7	3.5	13T * 12.7	3.8
9T * 15.88	4	13T * 15.88	4
9T * 19.05	3.5	13T * 19.05	3.5